# **Smart Switch** 2Node **User Manual**



#### 1 SETTING UP 2 NODE

It is smart Wi-fi enabled device that lets you control your lights & electronic devices from your Smart Phone from anywhere at any time.


AC Specifications	
Operating Input Power Range	100 VAC-240 VAC+-5%, 47-63 Hz
Maximum Load per Node	Resistive Loads: 500W / per Node (Convertional Incandescent and halogen ligh sources) Resistive-Capacitive Loads: 100 W /Per No (Fluorescent Tube lamp, CFL, and LED) LED loads maximum combination is 5 numbe per Node irrespective of waters.
General	Specifications
Power Consumption when loads off	<0.2 W
Power Consumption when loads on	<1.0 W
Temperature	Operation 0.C to +50.C. Storage -20 C to +70 C.
Relative Humidity	Operating 5%RH to 95%RH Non-Condensing Storage 5%RH to 95%RHNon-Condensing
Dimensions	49 mm x 43 mm x 23 mm
RF Frequency	2.4 GHz

### SETTING UP 2 NODE

Installation Process of 2 Node Smart Switch

Check the Wi-Fi signal strength at the switch board, signal strength should be good, Signal strength should Greater than -50 dBm. If it is less than - 50 dBm then adjust the router near to the switch board.


Open the switchboard top cover. Remove all the connections of the loads from the switch board and label them with numbers based on the load connection sequence to the switches. Identify and separate the neutral in the switch board.



#### SETTING UP 2 NODE

Take the Smart Switch product and connect the Neutral & Line to the input terminals. Connect all load wires to the output connector based on previous labels and load sequences. The outputs number should match with previous switches connections numbers.

Fit the product properly inside the switch hoard Verify all the connections including the Neutral and Line Connections, Load Sequence and inputs connections.



1. Download the SmartLife app onto your smartphone. This app available for both iOS and Android devices.



- 3. Enable the Location & Bluetooth in your mobile.

### 4 SETTING UP 2 NODE



Connect your mobile to 2.4 GHz Wi-Fi network.

#### 5 SETTING UP 2 NODE

- 4.After connecting the device, toggle the switch 7 times in 3 seconds duration until the indicator light starts blinking rapidly, until the indication RED LED blinks rapidly.
- 5. Ensure your phone's Bluetooth & Location are enabled.
- 6. Tap the icon "+" on the top right corner of the 'Smart Life' App, then select Auto Scan, and the device will be automatically discovered and click 'Go to add' on the prompt.
- 7. Tap the icon "+" besides the bluetooth device.







## SETTING UP 2 NODE

- Follow the app instructions to connect the 2 Node Smart Switch to your Wi-Fi network
- 9. Once connected, the app will prompt the connection. and click 'Done'
- 10. Now control the 2 Node through the 'Smart Life' App.
- 11.Once the configuration is completed successfully, the indicator light will turn off, and the device will be added to the 'Device List'.





Search and enable "Smart Life" Skill in Alexa and Google Home. Follow the on-screen instructions to complete the Voice Assistants Setup.

CONNECTING TO VOICE ASSISTANT







